



Accessori / Accessories / Accessoires / Zubehör

102151R	12-14" (140 mm.)	Mandrino / Chuck / Mandrin / Spannkreuz
102152R	13-15" (140 mm.)	Mandrino / Chuck / Mandrin / Spannkreuz
102153R	14-16" (140 mm.)	Mandrino / Chuck / Mandrin / Spannkreuz
102157R	16-18" (190 mm.)	Mandrino / Chuck / Mandrin / Spannkreuz
102154R	17.5-19.5" (220 mm.)	Mandrino / Chuck / Mandrin / Spannkreuz
102155R	19.5-22.5" (220 mm.)	Mandrino / Chuck / Mandrin / Spannkreuz
102156R	22.5-24.5" (250 mm.)	Mandrino / Chuck / Mandrin / Spannkreuz
103110	Guidafascia meccanico / Mechanical guiding unit / Dispositif mécanique de la chape / Mechanische Zentriervorrichtung	
103355	Faretto centratura battistrada / Spot light / Centreur lumineux de la chape / Licht zur Camelback-Zentrierung	
107271	Envelomatic / Envelopes applicator / Applicateur d'envelopes / Gummi-Hülle-Spreizer	
2130478	Graffatrice pneumatica per prestampato / Pneumatic stapler for precured tread / Agrafeuse pneumatique pour la bande de roulement / Pneum. Klammern-Einsatzgerät für vorgepressten Streifen	
2130479	Punti metallici per graffatrice 12 x 6 / Metal staples for stapler 12 x 6 / Points métalliques pour agrafeuse 12 x 6 / Metal-Klammern 12 x 6 für Klammern-Einsatzgerät	
2130480	Punti metallici per graffatrice 12 x 8 / Metal staples for stapler 12 x 8 / Points métalliques pour agrafeuse 12 x 8 / Metal-Klammern 12 x 8 für Klammern-Einsatzgerät	

Caratteristiche tecniche / Technical features / Caractéristiques techniques / Technische Daten

<ul style="list-style-type: none"> • 20 pneumatici vettura/h. - 10 pneumatici giganti/h. • P. 1150 mm. x L. 1200 mm. x H. 1200 mm. - P. Kg. 450 • Kw 0.55 - Kw 0.73 • ø min. 510 mm. - ø max. 1364 mm. sez. min. 120 mm. - sez. max. 457 mm. 	<ul style="list-style-type: none"> • 20 Car Tyres/h. - 10 Truck Tyres/h. • D. 1150 mm. x W. 1200 mm. x H. 1200 mm. - W. Kg. 450 • Kw 0.55 - Kw 0.73 • min. ø 510 mm. - max. ø 1364 mm. min. sect. 120 mm. - max. sect. 457 mm.
<ul style="list-style-type: none"> • 20 pneus tourisme/h. - 10 pneus camion/h. • P. 1150 mm. x L. 1200 mm. x H. 1200 mm. - P. Kg. 450 • Kw 0.55 - Kw 0.73 • ø min. 510 mm. - ø max. 1364 mm. sect. min. 120 mm. - sect. max. 457 mm. 	<ul style="list-style-type: none"> • 20 PKW-Reifen pro Stunde - 10 LKW-Reifen pro Stunde • L. 1150 mm. x B. 1200 mm. x H. 1200 mm. - G. Kg. 450 • Kw 0.55 - Kw 0.73 • min. Durchm. 510 mm. - max. Durchm. 1364 mm. min. Breite 120 mm. - max. Breite 457 mm.