

MATIC PMTC 50



103133 MATIC PMTC 50

Rullatrice automatica per pneumatici turismo da 10" a 16" completa di cerchi da 10".

Automatic building and stitching machine for 10" to 16" car tyres c/w 10" Alu-Rims.

Poseuse moleteuse de chape automatique pour pneus tourisme de 10" à 16" avec flasques en aluminium de 10".

Automatische Anroll- u. Belegemaschine für PKW-Reifen von 10 bis 16 Zoll komplett mit 10" Alu-Felgen.

Accessori / Accessories / Accessoires / Zubehör

103355	Faretto centratura battistrada / <i>Spot light</i> / <i>Centreur lumineux de la chape</i> / <i>Licht zur Camelback-Zentrierung</i>
103110	Guidafascia meccanico / <i>Mechanical guiding unit</i> / <i>Dispositif mécanique de la chape</i> / <i>Mechanische Zentriervorrichtung</i>
	Cerchi alluminio vedere pag. 58 / <i>Alu-Rims see page 58</i> / <i>Flasques en aluminium voir page 58</i> / <i>Alu-Felgen s. Seite 58</i>

Caratteristiche tecniche / Technical features / Caractéristiques techniques / Technische Daten

<ul style="list-style-type: none"> • 40/50 pneumatici/h. • P. 1500 mm. x L. 1700 mm. x H. 1750 mm. - P. Kg. 550 • Kw 0.55 - Kw 1.1 • ø min. 480 mm. - ø max. 800 mm. sez. min. 120 mm. - sez. max. 200 mm. 	<ul style="list-style-type: none"> • 40/50 tyres/h. • D. 1500 mm. x W. 1700 mm. x H. 1750 mm. - W. Kg. 550 • Kw 0.55 - Kw 1.1 • min. ø 480 mm. - max. ø 800 mm. min. sect. 120 mm. - max. sect. 200 mm.
<ul style="list-style-type: none"> • 40/50 pneus/h. • P. 1500 mm. x L. 1700 mm. x H. 1750 mm. - P. Kg. 550 • Kw 0.55 - Kw 1.1 • ø min. 480 mm. - ø max. 800 mm. sect. min. 120 mm. - sect. max. 200 mm. 	<ul style="list-style-type: none"> • 40/50 Reifen pro Stunde • L. 1500 mm. x B. 1700 mm. x H. 1750 mm. - G. Kg. 550 • Kw 0.55 - Kw 1.1 • min. Durchm. 480 mm. - max. Durchm. 800 mm. min. Breite 120 mm. - max. Breite 200 mm.